

LOW-ENERGY BOTTLE WASHING MACHINE

Technical Data CB 12-1-RV-8,2 VdF ng

Performance	bottles/h	8,000
Control range max.	bottles/h	8,400
Control range min.	bottles/h	4,000
Cycle time	sec.	5.4
Running time	min.	11.7
Bottle length up to	mm	308
Bottle diameter up to	mm	90
Bottles per row	pieces	12
Bottles inside the machine	pieces	1,548
Bottle cell carrier	pieces	134
Pre-heating:		
Total residence time	sec.	199.8
Treatment time effective	sec.	102.6
Caustic:		
Total residence time	min.	5.6
Bottles filled with caustic soak	min.	3.7
Cooling down area:		
Total residence time	min.	3.9
Treatment time effective	min.	1.9
Spraying time effective:		
Hot caustic	sec.	7.2
Caustic I	sec.	3.6
Caustic II	sec.	14.4
Warm-water I	sec.	14.4
Warm-water II	sec.	14.4
Cold-water	sec.	14.4
Fresh-water max.	sec.	14.4
Container contents:		
Pre-soaking	m ³	1.2
Caustic I	m ³	2.7
Caustic II	m ³	0.25
Warm-water I	m ³	0.25
Warm-water II	m ³	0.25
Cold-water	m ³	0.25
Water consumption for 0,5 l bottles	m ³ /h	1.6
Warm water consumption for 1 litre VdF bottles	m ³ /h	2.0
Warm water consumption for 1 litre VdF bottles with hot bottle discharge 55°C	m ³ /h	1.6
Heat consumption while heating the caustic from 15°C to 80°C (approx. value)	kJ x 1000	1,050
Heat consumption while operating, caustic 80°C (approx. value)	kJ/h x 1000	700
Heat consumption while operating, caustic 80°C for 1 litre VdF bottles with hot bottle discharge 55°C	kJ/h x 1000	580
Power connected load	kW	18
Operating weight	t	13

Consumption specifications refer to fresh-water 8-13°C, wastewater 35-43°C, bottle infeed 28-33°C, room temperature 15°C, bottle temperature at infeed 15°C

Exchange ratio: 1000 kJ \cong 238.8 kcal \cong 0.45 kg low pressure steam \cong 0.278 kWh

PAC Global GmbH, Germaniastrasse 40, CH-8006 Zurich, Switzerland

Phone: +41 (0) 44 / 252 96 33, German Phone: +49 (0) 170 / 811 33 80, Email: zimmermann@pacglobal.ch, www.pacglobal.ch